

EPOXIN-C

Surface Protection for Glass and Ceramic (Glazed) Surfaces



FEATURES

- ✓ It repels water and oil.
- ✓ It provides late contamination of the surface.
- ✓ Cleaned 80,000 times / 2 Years
- ✓ Transparent
- ✓ Protects the surface against chemicals
- ✓ Provides anti-icing.
- ✓ Provides UV protection.

CONTACT

- 🌐 www.epoxin.com.tr
- ✉ info@epoxin.com.tr
- ☎ +90 (216) 680 91 58



AREA OF USE

- ✓ Vehicle Glass Surfaces
- ✓ Shower Cabin Glass Surfaces
- ✓ Solar Panel Glass Surfaces
- ✓ Building Glass Surfaces
- ✓ Glazed Ceramic Surfaces

APPLICATION

- ✓ The surface should be cleaned of dirt, dust, water, oil and detergent residues before application and the application should be made on a dry surface
- ✓ The application should be made in a way that is not directly exposed to the sun. homogeneous spraying should be applied to an area of 0.5 m2 from a bottle with a trigger.
- ✓ Wipe the applied surface circularly with a cotton swab.
- ✓ Dryness to the touch: 3 hours, full curing is 24 hours.

PACKAGING

- ✓ 1 ltr covers 200 sqm
- ✓ 1 Ltr, 5 Ltr, 30 Ltr

