

EPOXIN-Z-WB

Water-based nano coating for absorbent mineral surfaces

FEATURES

- ✓ It repels water and oil.
- ✓ Provides UV protection.
- ✓ It provides late contamination of the surface.
- ✓ It does not prevent the surface from breathing.
- ✓ Protects the surface against chemicals.
- ✓ Reduces mildew and darkening.
- ✓ 3 years of protection

CONTACT

- 🌐 www.epoxin.com.tr
- ✉ info@epoxin.com.tr
- ☎ +90 (216) 680 91 58

AREA OF USE

- ✓ Absorbent Mineral Surfaces
- ✓ Absorbent Natural Stones
- ✓ Concrete Surfaces
- ✓ Tile, Brick and Floor tiles
- ✓ Chipped Crafts

APPLICATION

- ✓ The surface should be cleaned of dirt, dust, water, oil and detergent residues before application and the application should be done on a dry surface
- ✓ The application should be carried out in a way that is not directly exposed to the sun.
- ✓ Homogeneous spraying should be applied to an area of 0.5 m2 from a bottle with a trigger.
- ✓ Dryness to the touch 6 hours, full curing is 24 hours.

PACKAGING

- ✓ 1 ltr covers 10 sqm
- ✓ 1 Ltr, 5 Ltr, 30 Ltr

